

Code: 1008A - CS Ball Valve Three Piece Design Flanged End (300 Class)

Applicable Standard:

MFG. Standard: BS 5351/ API 608

Testing Standard: BS 5146 / API 598

Face to Face: ANSI B16.10

End Connection: ASME B16.5 RF 300 Class RF

Size Range: 15mm to 200mm (½ to 8 inch)

Max Working Temperature: 200 Deg. C



Pressure Rating : As Per 150 Class

Hydraulic Test Pressure

Body : 77 Kg/cm² (1125 psig)

Seat : 56 kg/cm² (815 psig)

Seat (Penumatic) : 07kg/cm²



Part Name	Material	QTY.
Body	CS to ASTM A216 Gr. WCB	01
Side Piece	CS to ASTM A216 Gr. WCB	02
Ball	AISI 304	01
Seat	PTFE / CFT /GFT	02
Body Seal	PTFE /CFT /GFT	02
Stem	AISI 304	01
Gland Seal	PTFE	03
Gland Bush	Stainless Steel	01
Stem Nut	Stainless Steel	01
Handle Nut	Stainless Steel	01
Handle	M.S.	01

CLASS - 300

SIZE		Ø NB	L End to End	Ø D Flange OD	FT Flange Thickness	Ø Rf Raised Faced	PCD	Ø d Hole Dia	N No. of Holes	Approx Weight Per Unit Kg.
inch	mm									
½ inch	15mm	15mm	140mm	95mm	14.2mm	35mm	66.5mm	16mm	04	1.8
¾ inch	20mm	20mm	152mm	117mm	15.7mm	43mm	82.5mm	19mm	04	3
1 inch	25mm	25mm	165mm	124mm	17.5mm	51mm	88.9mm	19mm	04	4
1 ¼ inch	32mm	32mm	178mm	133mm	19mm	64mm	98.5mm	19mm	04	5.5
1 ½ inch	40mm	40mm	190.5mm	155.5mm	20.5mm	73mm	114.3mm	22mm	04	6
2 inch	50mm	50mm	216mm	165mm	22mm	92mm	127mm	19mm	08	10
2 ½ inch	65mm	65mm	241mm	190.5mm	25mm	105mm	149.3mm	22mm	08	18
3 inch	80mm	80mm	282.5mm	209.5mm	28.5mm	127mm	168mm	22mm	08	24
4 inch	100mm	100mm	305mm	254mm	32mm	157mm	200mm	22mm	08	40
5 inch	125mm	125mm	381mm	279.4mm	35mm	186mm	235mm	22mm	08	85
6 inch	150mm	150mm	403mm	317.5mm	36.5mm	216mm	260.7mm	22mm	12	96
8 inch	200mm	200mm	419mm	381mm	41mm	270mm	330.2mm	25mm	12	140

